# **Connection Settings Guide**

Thank you for applying for Asahi Net WiMAX 2+ Service.

To start using W05, please configure connection settings following the steps 1-3 shown below.

# Insert au IC card to the router

Referring to Attaching/Removing au IC card in the Quick Start Guide, insert au IC card to the router.

\* The Quick Start Guide included in the box is in Japanese.

The English *Quick Start Guide* is available in the following webpage. https://asahi-net.jp/en/support/guide/mobile/wimax2plus/



## (2) Connect to Wi-Fi

Referring to Connecting by using Wi-Fi copy settings or Connecting manually in the Quick Start Guide, connect your devices (smartphones, computers, etc.) and the router with Wi-Fi.



#### How to switch to English display

- Slide the home screen and tap 設定 (Settings) to show システム設定 (Tools) screen.
- Select 言語 (Language.)
- Select English, and tap the check button at the top right to switch the display to English.



「言語」(Language)screen



# (3) Turn on the router and configure APN settings

Referring to the Steps to Configure APN Settings on the reverse side of the page, configure APN settings.

\* Please configure APN settings before you start using the router.

Proceed to the reverse side of the page



# **Steps to Configure APN Settings**

\* Please configure APN settings before you start using the router

## STEP 1

Lightly press the power button of the router, and the locked screen will appear. Slide up or down to unlock.



# STEP 2


Home screen will appear. Slide the screen and tap Settings.





# STEP 3

Settings screen will appear. Tap Profile management.



## STEP 4

Profile management screen will appear. Select  $AN01^*$ , then tap the check button at the top right.

\* If you are using a fixed IP address, select ANO2.



# Settings are completed.



If you have any questions, please contact us below:

# Asahi Net English Customer Support

Open hours: 10 a.m. to 5 p.m., Monday through Friday, excluding national holidays.

